

TC-3 Tire Cage Instructions

Thank you for purchasing a TrimmerTrap product. The TC-3 Tire Cages have been designed to help prevent lightweight equipment from rolling around in the truck or trailer while in transit. Depending on your purchase, you could have one or two different stand sizes and one to three different cage sizes. See a TrimmerTrap brochure or visit www.trimmertrap.com for information pertaining to the use of different size cages and stands for various size tires.

Attach the stand to a truck or trailer floor using the 1/2" carriage bolts and self locking nuts provided. To prevent a tripping hazard, install stands as close to the edge of the floor as possible. Be certain to leave enough clearance for the "L" handle threaded pin to be installed after installation. Slide the cage onto the stand and thread the "L" handle pin into cage. After deciding on the proper height for the cage, tighten securely. An optional pull pin is available for faster pre-determined height adjustments. To use the optional pull pin, you must drill a hole(s) into the stand(s) at the chosen height(s) for the pin to engage when released. When drilling a stand, use the cage as a guide to drill hole(s) in order to assure that the pin will align with the drilled hole(s). Be careful not to damage the threads on the cage. You also have the option of installing a padlock to prevent the cage from being raised by drilling a hole in the stand just above the cage. If a stand is used to store cages when not in use, it is recommended that a pull pin or padlock be used on the top cage to prevent accidental loss. This product is not in any way intended to replace tie downs or other devices used to secure equipment.

| <u>TC-3 Parts List</u> | <u>Quantity</u> | <u>Optional</u> |
|-------------------------------|------------------------|------------------------|
| 1/2" carriage bolts | two | 12" stand |
| 1/2" nylon lock nut | two | pull pin |
| "L" handle threaded pin | one | |
| 8" stand | one | |

*Each cage comes with an "L" handle threaded pin. Quantity and size of cage will be determined by which TC combination is ordered.

WARRANTY: 90 days against defects in material and workmanship, TrimmerTrap, Inc. reserves the right to repair or replace at its sole discretion the alleged defective TrimmerTrap product. Determination of validity of alleged defect claim will be made upon goods returned to us freight prepaid to our location in Louisville, KY. Call 1-800-279-8727 for a return goods authorization.